



EC DECLARATION OF PERFORMANCE

(System 3)

Issue No: **1**

13

Starglaze Windows & Conservatories Ltd.
Sternfenster upvc.
The Works,
Waterside South,
Lincoln,
LN5 7JD

This document declares that the product:

Aluminium French Door {Emergency Exit}

System Description: *Smarts Aluminium*


External pedestrian doorset, fitted with emergency exit panic hardware intended to be used in domestic and commercial buildings, on an escape routes.(1)

Essential Characteristics	Performance	Test Standards	Name, Address and Notified Body No of Test Laboratory	Test report reference and issue date
Watertightness	npd	BS EN 1027	N/A	N/A
Dangerous substances	None	BS EN 14351-1:2006+A1:2010	N/A	In house declaration
Resistance to wind load	npd	BS EN 12211	N/A	N/A
Impact resistance	npd	BS EN 13049	N/A	N/A
Load-bearing capacity of safety devices	Not Fitted	N/A	N/A	N/A
Height (mm)	npd	BS EN 14351-1:2006+A1:2010	N/A	N/A
Ability to release	npd	BS EN 179 and BS EN 1125	N/A	N/A
Acoustic performance	npd	BS EN ISO 140-3	N/A	N/A
Thermal transmittance	$\leq 1.8 \text{ Wm}^2\text{k}$	EN ISO 10077-1 & EN ISO 10077-2 (or EN ISO 12567-1 and prEN 12567-2)	Smarts WER	N/A
Radiation properties	npd	EN 410	N/A	N/A
Air permeability	npd	BS EN 1026	N/A	N/A
(1) Ability to release locked doors on escape routes. All emergency and Panic Escape devices comply with EN1125 & EN179 respectively. Continuous surveillance of Factory Production Control {FPC} in compliance with AVCP system 1 as per BS EN 14351-1:2006+A1:2010 Annex ZA by TUV notified test body No.0336. Report number 89204230				

This declaration of performance is issued under the sole responsibility of *Starglaze Windows & Conservatories Ltd.*


Signed on behalf of *Starglaze Windows & Conservatories Ltd* :

Signature:



Name and Position: M E Parczuk, Managing Director

Date: 18th December 2013

	
Starglaze Windows & Conservatories Ltd.	
13	
REF:Smarts PEF	
BS EN 14351-1:2006+A1:2010	
Notified Test Body 0336-CPR-89204230	
<i>Smarts Aluminium French Door</i>	
Intended for use on escape routes	
Water tightness	NPD
Notified Body / Certificate	0336-89204230
Dangerous substances	None
Resistance to wind load	NPD
Load bearing capacity of safety device	N/A
Acoustic performance	NPD
Thermal transmittance	$\leq 1.8 \text{ W/m}^2\text{K}$
Radiation properties	NPD
Air permeability	NPD